

› Model

AEG = Airette Gravity Ventilator

› Application

R = Relief
I = Intake

› Unit Material

A = Aluminum
G = Galvanized

› Filters

0 = None
A = 1" Aluminum Filters
C = 2" Aluminum Filters

› Screen

B = Galvanized Bird Screen
I = Aluminum Insect Screen
S = Insect/Bird Screen
L = Aluminum Bird Screen

› Insulated Hood

0 = None
A = 1" Fiberglass
X = Special

› Throat Access

0 = None
S = Split Throat
H = Hinged Hood (60" Max)

› Paint/Coating

0 = None
B = Air Dried Epoxy
Q = Air Dried Enamel
X = Special

› Color

0 = None
50 = Chrome Green
53 = Williamsburg Blue
55 = Pale Green
56 = Dove Gray
61 = White
63 = Oxford Beige
65 = Dover White
66 = Desert Tan
70 = Black
73 = Smoke Gray
77 = Brick Red
79 = Peppercorn
81 = Pale Brown
83 = Chocolate Brown
85 = Timeless Bronze
94 = Charcoal
X = Special

› Damper

0 = None
BDD = Gravity Backdraft Damper
CBD = Counter Balance Relief Damper
MD1 = Motor Operated Damper 115V
MD2 = Motor Operated Damper 230V
MD4 = Motor Operated Damper 460V
X = Special

› Roof Curb

0 = None	K = UCA18	Y = URA18
A = UCG8	L = UG12	1 = URG12
B = UCG12	N = SFG12	2 = URG18
C = UCG18	P = SFG18	X = Special
D = UCA8	T = UA12	
E = UCA12	U = UA18	
F = SFA12	V = UG18	
G = SFA18	W = URA12	

› Slope

0 = None
S = Single
D = Double

› Slope Side

0 = None
S = Short
L = Long

› Metal Liner

0 = None
L = Metal Liner

› Damper Holding Plate

0 = None
P = Damper Holding Plate

› Neoprene Gasket

0 = None
G = Gasket

› No Wooden Nailer

0 = Wood Nailer
N = No Wooden Nailer

› Curb Paint/Coating

0 = None
B = Air Dried Epoxy
Q = Air Dried Enamel
X = Special

› 125 MPH Construction

0 = None
X = Special

› AEG

Hooded Gravity Rooftop exhaust (relief or supply (fresh air) ventilator shall be Airette Gravity AEG, supplied by PennBarry, 1401 North Plano Road, Richardson, TX 75081.

Constructed of heavy gauge aluminum or galvanized throughout, hood roof is "cross braked" for water run off, hood ends are chamfered, and hood is sized to provide 100%, 150%, or 200% Free Area (depending on application). Hood is braced to support 30lb snow load. Hood is provided with galvanized bird screen, or optionally 1" washable (with some size limitations) filters.

Hood and throat joints are seam welded and caulked. Internal bracing is welded. Hood is mechanically fastened to throat for ease of removal. When properly guyed, unit will withstand 60 mph wind load, or optionally 125 MPH.