



PRODUCT SPECIFICATIONS

SAVE-T PVC Coated Polyester Fabric

10 OZ LAMINATED

Spec Sheet # 10L-3-07

| Material Description | | | | | | |
|------------------------------------|------|---|-------------|---------------------|-------------|-----------|
| Roll Dimensions | | English | | Metric | | |
| Material Weight | | 10 oz/yd ² (+/- 4%) | | 340 gr/sq.m (+/-4%) | | |
| Roll Width | | 61" | | 154.9cm | | |
| Roll Length | | 100 yards | | 91.44 meters | | |
| Net Weight | | 106 lbs | | 48.2 kg | | |
| Base Fabric | | | | | | |
| Fiber | | Polyester | | | | |
| Thickness | | .014" | | 0.36 m/m | | |
| Yarn (Denier) | | 250*500 | | - | | |
| Fabric Count (threads) | | 18/12 (fd/inch) | | - | | |
| Type of Coating | | S-PVC | | | | |
| Physical Properties | | | | | | |
| | | | | Test Method | | |
| | | English | Metric | FS-191 | ASTM | DIN |
| Tensile Strength (Strip Method) | Warp | 124 lbs/2" | 56 kg/5cm | FS 5102 | ASTM D 5035 | DIN 53354 |
| | Fill | 142 lbs/2" | 64.5 kg/5cm | | | |
| Tear Strength (Tongue Method) | Warp | 34 lbs | 15.5 kg | FS 5134 | ASTM D 2261 | DIN 53356 |
| | Fill | 26 lbs | 11.8 kg | | | |
| Adhesion Strength | | 19 lbs/2" | | FS 5970 | ASTM D 2724 | |
| Temperature Resistance | | -22 ~ +160°F | -30 ~ +70°C | - | ASTM D 2136 | DIN 53361 |
| Special Features | | UV For Exterior Applications, Mildew Resistant NFPA-701 Fire Rated | | | | |

Note: The information contained herein is believed to be reliable but no representations, guarantees or warranties of any kind are made as to its accuracy or suitability for particular applications.

TMI, LLC
 5350 Campbells Run Road
 Pittsburgh, PA 15205-9738
 Web-Site: www.tmivinylsolutions.com

Toll Free: 800-888-9750
 Phone: 412-787-9750
 Fax: 412-787-3665
 E-mail: vinylsolutions@tmi-pvc.com